

**Western Powders Inc**

**Accurate powders**

**Caliber: .338 Federal**

	<i>Bullet Weight Grains</i>	<i>Bullet make</i>	<i>Bullet Designation or type</i>	<i>Start Load (grains)</i>	<i>Start Velocity (Fps)</i>	<i>Max Load (grains)</i>	<i>Max Velocity</i>	<i>Max Pressure (psi)</i>	<i>COL (Inches)</i>
Barrel: 24"	Twist: 1 in 10"		Primer: WLR			Bullet diameter: .338"			
	Case length Min: 1.985"		Max: 2.000"	Max COL: 2.820"					
						<b>Reduced load</b>			
5744	200	Hornady	SP-Intlk	24.0	1675				
5744	200	Hornady	SP-Intlk	32.6	2200	36.2	2426	61000	2.814
2015	185	Barnes	TSX	38.9	2408	43.2	2593	58000	2.783
2015	200	Hornady	SP-Intlk	39.2	2369	43.5	2532	60500	2.814
2015	215	Sierra	SPBT	37.0	2242	41.1	2399	61200	2.800
2230	185	Barnes	TSX	40.9	2484	45.5	2683	60400	2.783
2230	200	Hornady	SP-Intlk	40.4	2376	44.8	2605	60900	2.814
2230	215	Sierra	SPBT	39.0	2317	43.3	2503	61000	2.800
2230	225	Nosler	Accubond	38.3	2261	42.5	2427	61200	2.814