

# LONG RANGE

## .308 WINCHESTER

Gun	HS PRECISION	Max Length	2.015"
Barrel Length	24"	Trim Length	1.995"
Primer	CCI 200	OAL Max	2.810"
Case	REM	OAL Min	2.490"

Bullet	START LOADS			MAXIMUM LOADS			C.U.P.	Cartridge Length	Comment
	Powder	Grains	Vel.	Powder	Grains	Vel.			
SRA 168 HPBT	<b>2015BR</b>	36.0	2325	<b>2015</b>	40.0	2642	50,500	2.800"	
	<b>2230</b>	37.8	2297	<b>2230</b>	42.0	2610	49,500		
	<b>2460</b>	38.3	2289	<b>2460</b>	42.5	2601	48,600		
	<b>2495</b>	40.1	2336	<b>2495</b>	44.5	2654	47,900		Compressed
	<b>2520</b>	40.5	2387	<b>2520</b>	45.0	2712	50,200		
	<b>2700</b>	42.3	2194	<b>2700</b>	47.0	2493	48,800		Compressed
SRA 175 HPBT	<b>2230</b>	36.0	2244	<b>2230</b>	40.0	2551	60,000*	2.800"	
	<b>2460</b>	36.4	2242	<b>2460</b>	40.5	2548	58,500*		
	<b>2520</b>	37.8	2285	<b>2520</b>	42.0	2597	61,000*		
	<b>4064</b>	39.1	2303	<b>4064</b>	43.5	2618	59,300*		
	<b>2700</b>	42.3	2280	<b>2700</b>	47.0	2591	57,800*		Compressed
SRA 180 HPBT	<b>2230</b>	36.0	2146	<b>2230</b>	40.0	2439	48,800	2.800"	
	<b>2460</b>	37.4	2177	<b>2460</b>	41.5	2474	49,500		
	<b>2495</b>	38.7	2281	<b>2495</b>	43.0	2592	50,800		
	<b>2520</b>	40.1	2302	<b>2520</b>	44.5	2616	49,200		
	<b>2700</b>	42.3	2174	<b>2700</b>	47.0	2470	40,000		Compressed
SRA 190 HPBT	<b>2230</b>	34.7	2084	<b>2230</b>	38.5	2368	47,700	2.800"	
	<b>2460</b>	35.1	2083	<b>2460</b>	39.0	2367	46,400		
	<b>2495</b>	36.0	2108	<b>2495</b>	40.0	2395	45,300		
	<b>2520</b>	37.4	2128	<b>2520</b>	41.5	2418	47,100		
	<b>2700</b>	40.5	2035	<b>2700</b>	45.0	2312	46,000		
SRA 220 HPBT	<b>2230</b>	32.4	1883	<b>2230</b>	36.0	2140	45,300	2.800"	
	<b>2460</b>	33.3	1911	<b>2460</b>	37.0	2172	46,200		
	<b>2495</b>	34.7	1959	<b>2495</b>	38.5	2226	47,300		
	<b>2520</b>	34.2	1896	<b>2520</b>	38.0	2154	44,900		
	<b>2700</b>	37.8	1900	<b>2700</b>	42.0	2159	48,300		

\* Pressure data in P.S.I.