

These loads are intended for low pressure applications <18000psi

<b>.45-70 GOVERNMENT - SPRINGFIELD TRAPDOOR</b>			
Gun	HS Precision	Case Max length	2.105 "
Barrel length	24"	Min length	2.085 "
Primer	CCI 200	COL max	2.550 "
Case	REM Nickel	COL min	2.490 "

Bullet	Start loads			Maximum loads			Cartridge length	Comment
	Powder	Grains	Vel.	Powder	Grains	Vel		
300 (L) PB	<b>5744</b>	27.9	1405	<b>5744</b>	31.0	1597	18500	2.550"
340 (L) HP	<b>5744</b>	27.0	1314	<b>5744</b>	30.0	1494	14600	2.520"
	<b>2495</b>	51.3	1628	<b>2495</b>	57.0	1850	18000	
378 (L) RNGC	<b>5744</b>	25.6	1247	<b>5744</b>	28.5	1418	15100	2.565"
	<b>2495</b>	45.0	1479	<b>2495</b>	50.0	1681	14500	
405 (L) FN	<b>5744</b>	24.3	1226	<b>5744</b>	27.0	1394	16100	2.550"
405 (L) PB	<b>5744</b>	24.7	1192	<b>5744</b>	27.5	1355	18800	2.550"
420 (L) FN	<b>5744</b>	25.6	1210	<b>5744</b>	28.5	1375	16100	2.600"
	<b>2495</b>	45.0	1457	<b>2495</b>	50.0	1656	17700	
475 (L) RNGC	<b>5744</b>	24.3	1102	<b>5744</b>	27.0	1253	18800	2.680"
	<b>2495</b>	40.5	1377	<b>2495</b>	45.0	1565	16000	
500 (L) FN	<b>5744</b>	23.4	1070	<b>5744</b>	26.0	1217	16100	2.635"
	<b>2495</b>	39.6	1348	<b>2495</b>	44.0	1532	18400	
520 (L) FN	<b>5744</b>	21.6	1060	<b>5744</b>	24.0	1205	16300	2.655"
530 (L) Postell	<b>5744</b>	20.1	1036	<b>5744</b>	22.4	1178	18600	2.950"
530 (L) RN	<b>5744</b>	25.6	1024	<b>5744</b>	28.5	1280	18400	2.830"
	<b>2495</b>	41.4	1237	<b>2495</b>	46.0	1406	11600	
570 (L) JONES	<b>5744</b>	19.8	949	<b>5744</b>	22.0	1079	18500	2.870"
400 SPR JSP	<b>5744</b>	23.4	1031	<b>5744</b>	26.0	1172	17200	2.560"