

.270 WINCHESTER

Gun	HS Precision	Case Max length	2.540 "
Barrel length	24"	Min length	2.520 "
Primer	REM 9 1/2	COL max	3.340 "
Case	REMINGTON	COL min	3.065 "

Bullet	Start loads			Maximum loads			CUP	Cartridge length	Comment
	Powder	Grains	Vel.	Powder	Grains	Vel			
150 (L) SPGC	5744	18.0	1624	5744	26.0	2125	31100	3.250"	Pressure in PSI
90 SRA HP	5744	36.0	2878	5744	40.0	3271	54500	3.090"	Pressure in PSI
	4064	47.7	3040	4064	53.0	3455	49600		
	2700	54.2	3245	2700	57.0	3452	52000		
	4350	53.0	3066	4350	58.0	3325	49900		
	3100	52.2	2652	3100	58.0	2943	44100		Compressed
100 HDY SP	5744	36.0	2735	5744	40.0	3108	54800	3.175"	Pressure in PSI
	4064	46.8	2938	4064	52.0	3339	50800		
	2700	53.2	3140	2700	56.0	3340	52000		
	4350	54.0	2953	4350	60.0	3356	48700		
	3100	52.2	2628	3100	58.0	2893	44200		Compressed

270 Winchester

Bullet	Start loads			Maximum loads			CUP	Cartridge length	Comment
	Powder	Grains	Vel.	Powder	Grains	Vel			
110 SRA SP	4064	45.9	2813	4064	51.0	3197	49000	3.240"	Compressed
	2700	52.3	3038	2700	55.0	3232	52000		
	4350	53.0	2900	4350	59.0	3300	52000		
	3100	52.2	2598	3100	58.0	2871	47200		
130 NOS BT	4064	43.2	2569	4064	48.0	2920	51200	3.330"	Compressed Pressure in Psi
	2700	49.4	2777	2700	52.0	2954	52000		
	4350	49.5	2660	4350	55.0	3020	52000		
	3100	52.2	2577	3100	58.0	2841	51500		
	Magpro	58.5	2919	Magpro	65.0	3234	63200		
130 BAR X-HP	4064	44.1	2557	4064	49.0	2906	49800	3.330"	Compressed Compressed
	2700	50.4	2765	2700	53.0	2941	51700		
	4350	52.2	2702	4350	58.0	3070	52000		
	3100	52.2	2616	3100	58.0	2811	48500		
140 HDY SBT	2700	49.4	2719	2700	52.0	2893	51600	3.330"	Compressed Compressed
	4350	50.4	2629	4350	56.0	2988	52000		
	3100	52.2	2598	3100	58.0	2791	49300		
150 SRA SBT	5744	30.6	2202	5744	34.0	2503	54600	3.300"	Pressure in PSI Compressed Pressure in psi
	2700	47.5	2574	2700	50.0	2738	52000		
	4350	47.0	2515	4350	53.0	2880	52000		
	3100	52.2	2547	3100	58.0	2769	52000		
	Magpro	55.4	2725	Magpro	61.5	3000	63600		
160 NOS (PART)	2700	47.5	2470	2700	50.0	2630	52000	3.335"	Compressed
	4350	47.2	2375	4350	52.5	2705	52000		
	3100	52.2	2511	3100	58.0	2744	52000		