

## .30-06 SPRINGFIELD

Gun	WILSON	Max Length	2.494"
Barrel Length	24"	Trim Length	2.474"
Primer	CCI 200	OAL Max	3.340"
Case	IMI	OAL Min	2.940"

Bullet	START LOADS			MAXIMUM LOADS			P.S.I.	Cartridge Length	Comment	
	Powder	Grains	Vel.	Powder	Grains	Vel.				
SRA 175 HPBT	<b>2015</b>	40.0	2359	<b>2015</b>	44.5	2681	58,800	3.290"	RP cases	
	<b>2230</b>	39.6	2323	<b>2230</b>	44.0	2640	59,500			
	<b>2460</b>	40.9	2334	<b>2460</b>	45.5	2653	58,700			
	<b>2520</b>	41.8	2341	<b>2520</b>	46.5	2661	57,000			
	<b>4064</b>	45.0	2456	<b>4064</b>	50.0	2792	57,900			
	<b>2700</b>	48.6	2429	<b>2700</b>	54.0	2761	58,200			
	<b>4350*</b>	51.3	2486	<b>4350</b>	57.0	2825	56,300			Compressed
	<b>3100*</b>	53.1	2341	<b>3100</b>	59.0	2661	48,800			Compressed
SRA 180 HPBT	<b>2015</b>	40.1	2277	<b>2015</b>	44.5	2588	59,300	3.290"		
	<b>2230</b>	39.6	2260	<b>2230</b>	44.0	2568	60,000			
	<b>2460</b>	41.2	2255	<b>2460</b>	45.8	2563	55,800			
	<b>2495</b>	41.0	2284	<b>2495</b>	45.5	2595	59,500			
	<b>2520</b>	42.1	2275	<b>2520</b>	46.8	2585	57,000			
	<b>2700</b>	49.5	2328	<b>2700</b>	55.0	2646	56,000			
	<b>4350</b>	51.3	2389	<b>4350</b>	57.0	2715	56,400			Compressed
	<b>3100</b>	53.1	2298	<b>3100</b>	59.0	2611	53,300			Compressed
SRA 190 HPBT	<b>2015</b>	38.7	2193	<b>2015</b>	43.0	2492	60,000	3.325"		
	<b>2230</b>	39.6	2180	<b>2230</b>	44.0	2477	56,600			
	<b>2460</b>	41.0	2233	<b>2460</b>	45.5	2537	58,400			
	<b>2495</b>	39.6	2193	<b>2495</b>	44.0	2492	59,100			
	<b>2520</b>	41.0	2212	<b>2520</b>	45.5	2514	58,400			
	<b>2700</b>	46.8	2217	<b>2700</b>	52.0	2519	53,700			
	<b>4350</b>	50.0	2343	<b>4350</b>	55.5	2663	60,000			Compressed
	<b>3100</b>	53.1	2265	<b>3100</b>	59.0	2574	53,200			Compressed

\* Loads can produce excessive port pressure in the M-1 Garand rifle and should not be used in this rifle.

## .300 HOLLAND & HOLLAND MAGNUM

Gun	DOUGLAS	Max Length	2.850"
Barrel Length	26"	Trim Length	2.820"
Primer	CCI 250	OAL Max	3.600"
Case	WW	OAL Min	3.420"

Bullet	START LOADS			MAXIMUM LOADS			C.U.P.	Cartridge Length	Comment
	Powder	Grains	Vel.	Powder	Grains	Vel.			
SRA 180 HPBT	<b>2700</b>	61.8	2729	<b>2700</b>	65.0	2903	51,400	3.640"	
	<b>4350</b>	63.5	2639	<b>4350</b>	70.5	2999	51,700		
	<b>3100</b>	70.2	2705	<b>3100</b>	78.0	3074	53,600		
SRA 200 HPBT	<b>2700</b>	58.0	2575	<b>2700</b>	61.0	2739	54,000	3.665"	
	<b>4350</b>	58.5	2479	<b>4350</b>	65.0	2817	51,000		
	<b>3100</b>	65.7	2563	<b>3100</b>	73.0	2912	52,900		