

Accurate LT-32

223 Remington

55000 Psi -- Standard SAAMI Commercial Specifications

Barrel: 24" | Twist: 1-12" | Primer: WSR | Bullet Diameter .224"

Case: WIN | Max Case Length: 1.760" | Trim Length: 1.750"

Powder	Bullet Info			Start Load		Max Load			COL
LT-32	40	HDY	V-MAX	22.0	3,313	24.4	3,659	54,690	2.260
LT-32	50	SIE	BK	21.0	3,018	23.3	3,336	54,805	2.260
LT-32	52	NOS	HPBT-CC	20.6	2,951	22.9	3,257	54,777	2.237
LT-32	55	HDY	V-MAX	20.0	2,857	22.2	3,129	54,997	2.260
LT-32	62	BAR	T-TSX	18.6	2,602	20.7	2,857	54,982	2.260
LT-32	68	HDY	BTHP	18.5	2,515	20.6	2,801	54,726	2.220
LT-32	77	SIE	HPBT	17.3	2,369	19.3	2,592	54,951	2.260

5.56X45 NATO

62350 PSI CIP Commercial and NATO/MIL Specification

Barrel: 24" | Twist: 1-7" | Primer: WSR | Bullet Diameter .224"

Case: WIN | Max Case Length: 1.760" | Trim Length: 1.750"

Powder	Bullet Info			Start Load		Max Load			COL
LT-32	40	HDY	V-MAX	23.0	3,457	25.5	3,820	61,877	2.260
LT-32	50	SIE	BK	21.9	3,149	24.4	3,481	61,889	2.260
LT-32	52	NOS	HPBT-CC	21.6	3,080	24.0	3,403	61,977	2.237
LT-32	55	HDY	V-MAX	21.0	2,979	23.3	3,265	61,887	2.260
LT-32	62	BAR	T-TSX	19.6	2,727	21.8	2,997	61,988	2.260
LT-32	68	HDY	BTHP	19.4	2,632	21.5	2,932	61,888	2.220
LT-32	77	SIE	HPBT	18.1	2,461	20.1	2,696	61,944	2.260

6mm PPC

Barrel: 24" | Twist: 1-14" | Primer: REM 7 1/2 | Bullet Diameter .243"

Case: NORMA | Max Case Length: 1.503" | Trim Length: 1.493"

Powder	Bullet Info			Start Load		Max Load			COL
LT-32	55	NOS	B-TIP	27.0	3,225	30.0	3,588	58,877	2.100
LT-32	68	BAR	FB	25.3	2,898	28.2	3,222	58,899	2.105
LT-32	68	BRG	HP	25.0	2,844	27.7	3,130	57,896	2.105
LT-32	70	BRG	FB	25.1	2,862	27.9	3,169	58,666	2.105
LT-32	70	SIE	HPBT	24.7	2,850	27.5	3,163	58,799	2.088

6mm BR Remington

Barrel: 24" | Twist: 1-14" | Primer: REM 7 1/2 | Bullet Diameter .243"

Case: REM | Max Case Length: 1.560" | Trim Length: 1.550"

Powder	Bullet Info			Start Load		Max Load			COL
LT-32	58	HDY	V-MAX	28.3	3,304	31.5	3,654	58,614	2.140
LT-32	60	BRG	FB	28.0	3,272	31.1	3,597	58,498	2.140
LT-32	65	HDY	V-MAX	29.3	3,379	29.9	3,439	58,732	2.150
LT-32	68	BAR	FB	26.6	3,040	29.6	3,363	58,729	2.150
LT-32	70	BRG	FB	26.6	3,019	29.5	3,319	58,609	2.150
LT-32	70	SIE	HPBT	26.2	3,026	29.1	3,316	58,737	2.150
LT-32	87	HDY	V-MAX	24.7	2,691	27.4	2,958	58,553	2.160